

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Date of issue: 16/05/2017 Revision date: 16/05/2017

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article
Product name : Whiteboard User Kit / Deluxe
Product code : 1901430; 1901431

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use, Consumer use
Use of the substance/mixture : Whiteboard Cleaner
Whiteboard marker pen for large text

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Acco UK Ltd.
Oxford House, Oxford Road,
Aylesbury, Bucks,
HP21 8SZ.

Telephone: +44 (0) 844 209 8360 (9am to 5pm)
Fax: +44 (0) 845 603 1731
Website: www.acco.co.uk
Email: informationeurope@acco.com

1.4. Emergency telephone number

Emergency number : 0844 2098360

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
United Kingdom	National Poisons Information Service (NHS Direct)	http://www.npis.org	111 (England & Wales only) or 112 (EU) or 08454 24 24 24 (Scotland)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
2
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 1 H318

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS05



Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Signal word (CLP)	: Danger
Hazardous ingredients	: disodium metasilicate
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour H315 - Causes skin irritation H318 - Causes serious eye damage
Precautionary statements (CLP)	: P102 - Keep out of reach of children P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P280 - Wear eye protection, protective gloves, protective clothing P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a POISON CENTER or doctor P362+P364 - Take off contaminated clothing and wash it before reuse P501 - Dispose of contents to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation
Security closing plug for children	: Not applicable
Tactile warning	: Applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, ES, FI, FR, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK)	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43-XXXX	>= 50	Flam. Liq. 2, H225
propan-2-ol, isopropyl alcohol, isopropanol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119457558-25-XXXX	< 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
3-butoxypropan-2-ol, propylene glycol monobutyl ether	(CAS-No.) 5131-66-8 (EC-No.) 225-878-4 (EC Index-No.) 603-052-00-8	1 - 15	Skin Irrit. 2, H315 Eye Irrit. 2, H319
disodium metasilicate	(CAS-No.) 6834-92-0 (EC-No.) 229-912-9 (EC Index-No.) 014-010-00-8	1 - 15	Skin Corr. 1B, H314 STOT SE 3, H335

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanol (64-17-5)		
Austria	Local name	Ethanol
Austria	MAK (mg/m ³)	1900 mg/m ³
Austria	MAK (ppm)	1000 ppm
Austria	MAK Short time value (mg/m ³)	3800 mg/m ³
Austria	MAK Short time value (ppm)	2000 ppm
Belgium	Local name	Alcool éthylique # Ethanol
Belgium	Limit value (mg/m ³)	1907 mg/m ³
Belgium	Limit value (ppm)	1000 ppm
Bulgaria	Local name	Етилов алкохол
Bulgaria	OEL TWA (mg/m ³)	1000 mg/m ³

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethanol (64-17-5)		
Croatia	Local name	Etanol; (Etil-alkohol)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	1900 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	1000 ppm
Croatia	Naznake (HR)	F (lako zapaljivo)
Czech Republic	Local name	Ethanol
Czech Republic	Expoziční limity (PEL) (mg/m ³)	1000 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	530 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	3000 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	1600 ppm
Denmark	Local name	Ethanol (Ethylalkohol)
Denmark	Grænseværdie (langvarig) (mg/m ³)	1900 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Estonia	Local name	Etanool (etüülalkohol)
Estonia	OEL TWA (mg/m ³)	1000 mg/m ³
Estonia	OEL TWA (ppm)	500 ppm
Estonia	OEL STEL (mg/m ³)	1900 mg/m ³
Estonia	OEL STEL (ppm)	1000 ppm
Finland	Local name	Etanoli
Finland	HTP-arvo (8h) (mg/m ³)	1900 mg/m ³
Finland	HTP-arvo (8h) (ppm)	1000 ppm
Finland	HTP-arvo (15 min)	2500 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1300 ppm
France	Local name	Alcool éthylique
France	VME (mg/m ³)	1900 mg/m ³
France	VME (ppm)	1000 ppm
France	VLE (mg/m ³)	9500 mg/m ³
France	VLE (ppm)	5000 ppm
France	Note (FR)	Valeurs recommandées/admises
Germany	Local name	Ethanol
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	960 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	500 ppm
Germany	Remark (TRGS 900)	DFG, Y
Greece	OEL TWA (mg/m ³)	1900 mg/m ³
Greece	OEL TWA (ppm)	1000 ppm
Hungary	Local name	ETIL-ALKOHOL
Hungary	AK-érték	1900 mg/m ³
Hungary	CK-érték	7600 mg/m ³
Hungary	Megjegyzések (HU)	IV.
Ireland	Local name	Ethanol
Ireland	OEL (15 min ref) (ppm)	1000 ppm
Latvia	Local name	Etilspirts (etanols)
Latvia	OEL TWA (mg/m ³)	1000 mg/m ³
Lithuania	Local name	Etanolis (etilo alkoholis)
Lithuania	IPRV (mg/m ³)	1000 mg/m ³
Lithuania	IPRV (ppm)	500 ppm
Lithuania	TPRV (mg/m ³)	1900 mg/m ³
Lithuania	TPRV (ppm)	1000 ppm
Netherlands	Local name	Ethanol

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethanol (64-17-5)		
Netherlands	Grenswaarde TGG 8H (mg/m ³)	260 mg/m ³
Netherlands	Grenswaarde TGG 8H (ppm)	136 ppm (Ethanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	1900 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (ppm)	992 ppm (Ethanol; Netherlands; Short time value; Public occupational exposure limit value)
Netherlands	Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een Haanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Poland	Local name	Etanol (alkohol etylowy)
Poland	NDS (mg/m ³)	1900 mg/m ³
Portugal	Local name	Etanol (Álcool etílico)
Portugal	OEL STEL (ppm)	1000 ppm
Romania	Local name	Alcool etilic
Romania	OEL TWA (mg/m ³)	1900 mg/m ³
Romania	OEL TWA (ppm)	1000 ppm
Romania	OEL STEL (mg/m ³)	9500 mg/m ³
Romania	OEL STEL (ppm)	5000 ppm
Slovakia	Local name	Etylalkohol (etanol)
Slovakia	NPHV (priemerná) (mg/m ³)	960 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	500 ppm
Slovakia	OEL STEL (mg/m ³)	1920 mg/m ³
Slovakia	OEL STEL (ppm)	1000 ppm
Slovenia	Local name	etanol (etilalkohol)
Slovenia	OEL TWA (mg/m ³)	1900 mg/m ³
Slovenia	OEL TWA (ppm)	1000 ppm
Slovenia	OEL STEL (mg/m ³)	7600 mg/m ³
Slovenia	OEL STEL (ppm)	4000 ppm
Spain	Local name	Etanol (Alcohol etílico)
Spain	VLA-EC (mg/m ³)	1910 mg/m ³
Spain	VLA-EC (ppm)	1000 ppm
Spain	Notes	s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltese: Base de datos de productos biocidas: http://www.msssi.gob.es/ciudadanos/productos.do?tip o=plaguicidas Base de datos de productos fitosanitarios http://www.magrama.gob.es/agricultura/pags/fitos/regi stro/fichas/pdf/Lista_sa.pdf).
Sweden	Local name	Etanol
Sweden	nivågränsvärde (NVG) (mg/m ³)	1000 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	500 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	1900 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	1000 ppm
Sweden	Anmärkning (SE)	V (Vägledande kortidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
United Kingdom	Local name	Ethanol

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethanol (64-17-5)		
United Kingdom	WEL TWA (mg/m ³)	1920 mg/m ³
United Kingdom	WEL TWA (ppm)	1000 ppm
Iceland	Local name	Etanól (etýlalkóhól)
Iceland	OEL (8 hours ref) (mg/m ³)	1900 mg/m ³
Iceland	OEL (8 hours ref) (ppm)	1000 ppm
Norway	Local name	Etanol
Norway	Grenseverdier (AN) (mg/m ³)	950 mg/m ³
Norway	Grenseverdier (AN) (ppm)	500 ppm
Switzerland	Local name	Ethanol
Switzerland	MAK (mg/m ³)	960 mg/m ³ 960 mg/m ³
Switzerland	MAK (ppm)	500 ppm 500 ppm
Switzerland	KZGW (mg/m ³)	1920 mg/m ³ 1920 mg/m ³
Switzerland	KZGW (ppm)	1000 ppm 1000 ppm
Switzerland	Remark (CH)	SS _C - OAW, Formal ^{KT HU} - INRS, NIOSH
Australia	Local name	Ethyl alcohol
Australia	TWA (mg/m ³)	1880 mg/m ³ Synonym (Ethanol)
Australia	TWA (ppm)	1000 ppm Synonym (Ethanol)
USA - ACGIH	Local name	Ethanol
USA - ACGIH	ACGIH STEL (ppm)	1000 ppm
USA - ACGIH	Remark (ACGIH)	URT irr
USA - OSHA	Local name	Ethyl alcohol (Ethanol)
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)		
Austria	Local name	2-Propanol Kurzzeitwert für Großguss
Austria	MAK (mg/m ³)	500 mg/m ³
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m ³)	2000 mg/m ³
Austria	MAK Short time value (ppm)	800 ppm
Belgium	Local name	Alcool isopropylique # Isopropylalcohol
Belgium	Limit value (mg/m ³)	500 mg/m ³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m ³)	1000 mg/m ³
Belgium	Short time value (ppm)	400 ppm
Bulgaria	Local name	Изопропилов алкохол
Bulgaria	OEL TWA (mg/m ³)	980 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	1225 mg/m ³
Croatia	Local name	Propan-2-ol; (izopropil-alkohol; izopropanol)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	999 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	400 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	1250 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	500 ppm
Croatia	Naznake (HR)	F (lako zapaljivo); Xi (nadražujuće)
Czech Republic	Local name	iso-Propanol
Czech Republic	Expoziční limity (PEL) (mg/m ³)	500 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	204 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	1000 mg/m ³

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)		
Czech Republic	Expoziční limity (NPK-P) (ppm)	410 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Isopropylalkohol (Isopropanol; 2-Propanol; sec-Propylalkohol)
Denmark	Grænseværdie (langvarig) (mg/m ³)	490 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Estonia	Local name	2-propanool (isopropüülalkohol, isopropanool)
Estonia	OEL TWA (mg/m ³)	350 mg/m ³
Estonia	OEL TWA (ppm)	150 ppm
Estonia	OEL STEL (mg/m ³)	600 mg/m ³
Estonia	OEL STEL (ppm)	250 ppm
Finland	Local name	2-Propanoli
Finland	HTP-arvo (8h) (mg/m ³)	500 mg/m ³
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	620 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	250 ppm
France	Local name	Alcool isopropylique
France	VLE (mg/m ³)	980 mg/m ³
France	VLE (ppm)	400 ppm
France	Note (FR)	Valeurs recommandées/admises
Germany	Local name	Propan-2-ol
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	500 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm
Germany	Remark (TRGS 900)	DFG, Y
Greece	OEL TWA (mg/m ³)	980 mg/m ³
Greece	OEL TWA (ppm)	400 ppm
Greece	OEL STEL (mg/m ³)	1225 mg/m ³
Greece	OEL STEL (ppm)	500 ppm
Hungary	Local name	IZOPROPIL-ALKOHOL
Hungary	AK-érték	500 mg/m ³
Hungary	CK-érték	2000 mg/m ³
Hungary	Megjegyzések (HU)	b, i; II.1.
Ireland	Local name	Isopropyl alcohol
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Ireland	Notes (IE)	Sk
Latvia	Local name	Izopropanols (2-propanols, izopropilspirts, 1-metil-1-etanols)
Latvia	OEL TWA (mg/m ³)	350 mg/m ³
Latvia	OEL STEL (mg/m ³)	600 mg/m ³
Lithuania	Local name	2-propanolis (izopropanolis, izopropilo alkoholis)
Lithuania	IPRV (mg/m ³)	350 mg/m ³
Lithuania	IPRV (ppm)	150 ppm
Lithuania	TPRV (mg/m ³)	600 mg/m ³
Lithuania	TPRV (ppm)	250 ppm
Poland	Local name	Propan-2-ol (izopropylowy alkohol)
Poland	NDS (mg/m ³)	900 mg/m ³
Poland	NDSch (mg/m ³)	1200 mg/m ³

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)		
Portugal	Local name	2-Propanol (isopropanol ou álcool isopropílico)
Portugal	OEL TWA (ppm)	200 ppm
Portugal	OEL STEL (ppm)	400 ppm
Romania	Local name	Alcool izopropilic
Romania	OEL TWA (mg/m ³)	200 mg/m ³
Romania	OEL TWA (ppm)	81 ppm
Romania	OEL STEL (mg/m ³)	500 mg/m ³
Romania	OEL STEL (ppm)	203 ppm
Slovakia	Local name	Izopropylalkohol (propán-2-ol)
Slovakia	NPHV (priemerná) (mg/m ³)	500 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Slovakia	OEL STEL (mg/m ³)	1000 mg/m ³
Slovakia	OEL STEL (ppm)	400 ppm
Slovenia	Local name	propan-2-ol (izopropilalkohol; izopropanol)
Slovenia	OEL TWA (mg/m ³)	500 mg/m ³
Slovenia	OEL TWA (ppm)	200 ppm
Slovenia	OEL STEL (mg/m ³)	2000 mg/m ³
Slovenia	OEL STEL (ppm)	800 ppm
Spain	Local name	Isopropanol (Alcohol isopropílico)
Spain	VLA-ED (mg/m ³)	500 mg/m ³
Spain	VLA-ED (ppm)	200 ppm
Spain	VLA-EC (mg/m ³)	1000 mg/m ³
Spain	VLA-EC (ppm)	400 ppm
Spain	Notes	VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento), s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltese: Base de datos de productos biocidas: http://www.msssi.gob.es/ciudadanos/productos.do?tip o=plaguicidas Base de datos de productos fitosanitarios http://www.magrama.gob.es/agricultura/pags/fitos/regi stro/fichas/pdf/Lista_sa.pdf).
Sweden	Local name	Isopropanol
Sweden	nivågränsvärde (NVG) (mg/m ³)	350 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	150 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	600 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
Sweden	Anmärkning (SE)	V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
United Kingdom	Local name	Propan-2-ol
United Kingdom	WEL TWA (mg/m ³)	999 mg/m ³
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m ³)	1250 mg/m ³
United Kingdom	WEL STEL (ppm)	500 ppm
Norway	Local name	2-propanol (Isopropanol)
Norway	Grenseverdier (AN) (mg/m ³)	245 mg/m ³
Norway	Grenseverdier (AN) (ppm)	100 ppm
Switzerland	Local name	Isopropanol (s. 2-Propanol)

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)		
Switzerland	MAK (mg/m ³)	500 mg/m ³ 500 mg/m ³ 500 mg/m ³ 500 mg/m ³
Switzerland	MAK (ppm)	200 ppm 200 ppm 200 ppm 200 ppm
Switzerland	KZGW (mg/m ³)	1000 mg/m ³ 1000 mg/m ³ 1000 mg/m ³ 1000 mg/m ³
Switzerland	KZGW (ppm)	400 ppm 400 ppm 400 ppm 400 ppm
Switzerland	Remark (CH)	B SS _c - Auge & OAW, ZNS, Leber ^{KT AN} - INRS, NIOSH
Australia	Local name	Isopropyl alcohol
Australia	TWA (mg/m ³)	983 mg/m ³ Synonym (Propan-2-ol)
Australia	TWA (ppm)	400 ppm Synonym (Propan-2-ol)
Australia	STEL (mg/m ³)	1230 mg/m ³ Synonym (Propan-2-ol)
Australia	STEL (ppm)	500 ppm Synonym (Propan-2-ol)
USA - ACGIH	Local name	2-Propanol
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	400 ppm
USA - ACGIH	Remark (ACGIH)	Eye & URT irr; CNS impair
USA - OSHA	Local name	Isopropyl alcohol
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	400 ppm

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure. Gloves. Safety glasses. Protective clothing.
Hand protection	: In case of repeated or prolonged contact wear gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Freezing point	: No data available
Boiling point	: 78 °C
Flash point	: 12 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ethanol (64-17-5)	
LD50 oral rat	10740 mg/kg bodyweight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)
3-butoxypropan-2-ol, propylene glycol monobutyl ether (5131-66-8)	
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (ppm)	> 651 ppm/4h (Rat; Experimental value)
disodium metasilicate (6834-92-0)	
LD50 dermal rat	> 5000 mg/kg bodyweight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Whiteboard User Kit / Deluxe

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

ethanol (64-17-5)	
LC50 fish 1	14200 mg/l (LC50; US EPA; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
LC50 fish 2	9640 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 2	13299 mg/l (EC50; Other; 48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (EC50; UBA; 72 h; Scenedesmus subspicatus)
disodium metasilicate (6834-92-0)	
LC50 fish 1	210 mg/l (LC50; Equivalent or similar to OECD 203; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 1	207 mg/l (EC50; DIN 38412-9; 72 h; Scenedesmus subspicatus; Fresh water)

12.2. Persistence and degradability

ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in soil. Very mobile in soil.
Biochemical oxygen demand (BOD)	0,8 - 0,967 g O ₂ /g substance
Chemical oxygen demand (COD)	1,7 g O ₂ /g substance
ThOD	2,1 g O ₂ /g substance
BOD (% of ThOD)	0,43
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in soil. Biodegradable in soil in anaerobic condition. No (test)data available on mobility of the substance.
Biochemical oxygen demand (BOD)	1,19 g O ₂ /g substance
Chemical oxygen demand (COD)	2,23 g O ₂ /g substance
ThOD	2,4 g O ₂ /g substance
3-butoxypropan-2-ol, propylene glycol monobutyl ether (5131-66-8)	
Persistence and degradability	Readily biodegradable in water. No (test)data available on mobility of the substance.
disodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: Not applicable. No (test)data available on mobility of the substance.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

ethanol (64-17-5)	
BCF fish 1	1 (BCF; Other; 72 h; Cyprinus carpio; Static system; Fresh water; Read-across)
Log Pow	-0,31 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Log Pow	0,05 (Weight of evidence approach; Other; 25 °C)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3-butoxypropan-2-ol, propylene glycol monobutyl ether (5131-66-8)	
Log Pow	0,98 (QSAR)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

disodium metasilicate (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: Not applicable.

12.4. Mobility in soil

ethanol (64-17-5)	
Surface tension	0,022 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Read-across

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Surface tension	0,021 N/m (25 °C)

3-butoxypropan-2-ol, propylene glycol monobutyl ether (5131-66-8)	
Surface tension	0,0276 N/m (20 °C; 100 %)

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1993	1993	1993	1993	1993
14.2. UN proper shipping name				
FLAMMABLE LIQUID, N.O.S. (ethanol)	FLAMMABLE LIQUID, N.O.S. (ethanol)	Flammable liquid, n.o.s. (ethanol)	FLAMMABLE LIQUID, N.O.S. (ethanol)	FLAMMABLE LIQUID, N.O.S. (ethanol)
Transport document description				
UN 1993 FLAMMABLE LIQUID, N.O.S. (ethanol), 3, II, (D/E)	UN 1993 FLAMMABLE LIQUID, N.O.S. (ethanol), 3, II	UN 1993 Flammable liquid, n.o.s. (ethanol), 3, II	UN 1993 FLAMMABLE LIQUID, N.O.S. (ethanol), 3, II	UN 1993 FLAMMABLE LIQUID, N.O.S. (ethanol), 3, II
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601, 640D
Limited quantities (ADR)	: 11

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
-------------------------------	-------

- Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

- Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3H

- Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 274, 601, 640D
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

- Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 274, 601, 640D
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001

Whiteboard User Kit / Deluxe Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance on the REACH candidate list

15.1.2. National regulations

Germany

VwVwS Annex reference	: Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV	: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen	: ethanol is listed
SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: ethanol is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: ethanol is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: ethanol is listed

Denmark

Class for fire hazard	: Class I-1
Store unit	: 1 liter
Classification remarks	: F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed
Recommendations Danish Regulation	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation



Whiteboard User Kit / Deluxe

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

SDS EU_NSC

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.